


Ascend



Technical Specifications

Style Name	Ascend
Construction	Multi-Level Loop
Fiber	100% PP
Gauge	1/12"
Stitches	10 per inch
Pile Weight	20 OZ/yd ²
Average Pile Height	4 mm±0.5 mm
Backing	E+bac
Tile Size	25cm*100cm
Installation Method	



Performance Specifications

	Test Code	Standard	Test Results	
Flammability Tests				
Radiant Panel	ASTM E 648	Class II	Class II	Pass
Smoke Density	ASTM E 662	Density ≤ 450	≤ 450	Pass
Stability				
Delamination	ASTM D3936	≥3.0 lbc/in		
Dimensional Stability	AACHEN	≤0.2%	≤0.2%	Pass
Tuft Bind	ASTM D1335	≥8.0 lbs	≥8.0 lbs	
Anti-Static				
Static Propensity	AATCC 134	≤3.5 kV	≤3.5 kV	Pass
Colour Fastness				
Light	AATCC 16 E	≥4-5	4-5	Pass
Water	AATCC 107	≥4-5	4-5	Pass
Rubbing/Crocking	AATCC 165	≥4-5	4-5	Pass
Generic Tests				
Green Carpet(VOC)	GLP 100036 [#]		Accredited	

NOTE: All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. Product Specifications may be changed without notice as long as product performance is not materially affected.